



Part Number: 6616

XTC 6000 thin client

Performance Class Thin Client

The XTC 6000 offers a combination of high performance and expandability. Powered by a 1.6GHz VIA Eden ULV processor, this unit is powerful, energy efficient and secure.

Designed for easy expansion and capable of dual monitors and rich multi media graphics, the XTC 6000 provides a superior end user experience.



✓ XPe Operating System	✓ Centralized Management
✓ No Moving Parts	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
✓ Multiple Level Lock Down Feature with Protected File System	✓ Wide Screen Support
✓ IE6 (*7 available upon request)	✓ 1600 X 1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built in Kensington Security Lock
✓ Energy Efficient	✓ Dual Monitor Support
✓ BlueZone Desktop Terminal Emulation	✓ Windows Embedded Standard available upon request

**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**





System

Operating System	XPe SP2 (Windows Embedded Standard 2009 available upon request)
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Eden ULV 1.6 GHz
Browser	IE6 (**7 or 8 available upon request)
Video Resolution	Up to 1600 x 1200 x 32 bit color
Wide Screen Support	•

Memory

RAM (Stand/MAX)	512MB/2GB
Storage (Stand/MAX)	512MB/16GB

Software Configuration

Host Access	Supports TN5250e/TN3270e, SSL, IBM 3151, (BlueZone Desktop) VT100 and VT200, SCOANSI and others*
ICA	Version 11 with HDX
RDP	6.1
Client Software	<ul style="list-style-type: none"> Adobe Acrobat Viewer 7 (**8 or 9 available upon request) Adobe Flash Player 10 MS Office Viewers 2003 (2007 available upon request) Microsoft Outlook Express Windows Media Player 11 Shockwave 11.5 Sun JVM 1.42 (1.6 upon request) & MS Java VNC Shadowing
VDI Clients	Optional Quest vWorkspace V6.2, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View V3.1.2 and 2X VirtualDesktopServer

Dimensions

Device	2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm
Weight	3.7 lbs. (1.7kg)

Audio

Mic In/Line Out	•
Speaker	x 1 (built in 1W internal Speaker)

Management

10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Update of Firmware	•
Recover Image	•
Configuration of Various Connection Types including 5250	•

Ports

USB Ports Type 2	4
PS2 Port	Keyboard and mouse via 'Y' cable
Serial Port (D Sub, 9 Pin Male Connector)	2 ***
Parallel Port	1***

Environmental

Operating Temperature	0° ~ 40°C 32° ~ 104°F
Operating Humidity	20% ~ 90% non condensing

Power

Consumption	15 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
--	---

Compliance

	RoHS
	WEEE
	CE
	FCC

Features

Security Features	<ul style="list-style-type: none"> Kensington Security Lock Slot Auto start/auto restart connection, Multiple level lock down user interface Administrative and user passwords
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
6616NE	XTC 6000, XPe, IE6 SP2, Sun JVM & MS Java, RCP, ICA, Shockwave, Flashplayer, Optical Mouse, Adobe Acrobat Viewer, MS Office Viewers, MS Outlook Express and Windows Media Player.
6616	Featured software from 6616NE plus BlueZone Desktop Emulation
9001	USB to Centronics
9011	PCI Expansion Card (Serial and Parallel Port)
9009	Internal Wireless (802.11 b/g)
9010	Internal Wireless (802.11 b/g/n + Cisco)
8122b	122 Key Driverless PC Keyboard
8104b	104 Key PC Keyboard
8008	1 GB DOM (Call for Customization and other Embedded Applications)

** Requires 1GB DOM IE 7 or 8, Sun JVM 1.6, Adobe 8 or 9 (IE 8 available on WES)

*VT320, VT420, VT52, WYSE60, WYSE60/AIF, VAX/AIX, LINUX, HP70094/8, HP70092/6, HP2392A

*** One parallel and one serial port available with optional PCI card (9011)

